



PAPYRUS
Fireplace
tool sets
See page 38

NEW

1700

OB01700

BEYOND

ELEGANCE

Osburn 1700 with brushed nickel plated cast iron structural leg kit and brushed nickel door overlay.

Emissions
1.26 g/h

Optimum efficiency
78%

Maximum heat output
65,000 BTU/h

Designed to meet the needs of smaller spaces, the Osburn 1700 is a faithful copy of the recently redefined 2000 model. This firebox combines robustness and elegance to allow you to enjoy your heating experience with confidence. This unit is equipped with high-density bricks, a cast iron door, a built-in ash pan, a top heat deflector that redirects heat to the front of the unit, and side panels to reduce its clearances.

Choose your favorite version by customizing the unit to suit your style: refined door overlays, new leg designs, glass ash lip. Respecting the most stringent legislation on particle emissions with only 1.26 g/h, this wood stove is perfect for those looking to go further.

RECOMMENDED HEATING AREA: 500 - 1,800 sq. ft.*

FIREBOX VOLUME: 1.9 cu. ft.

OVERALL DIMENSIONS (PEDESTAL): 30 3/8" H x 24 7/8" W x 23 1/4" D

MAXIMUM LOG LENGTH: 18"

REQUIRED ACCESSORIES

- > Black or brushed nickel door overlay
- > Choice of pedestal, black or brushed nickel cast iron legs with ash pan kit

OPTIONS

- > 130 CFM blower with variable speed control (thermodisc included)
- > 5"Ø fresh air intake kit
- > Rigid fire screen
- > Glass ash lip

Choice of legs



Pedestal



*See the complete technical data on pages 17 and 18. **See note 2 on page 17.