



NEW

Osburn 1700 insert with brushed nickel plated door overlay and black faceplate trims.

Emissions
1.26 g/h

Optimum efficiency
78%

Maximum heat output
65,000 BTU/h

1700
Insert

OB01705

BEYOND

SIZE

Like its larger counterpart Osburn 2000, the 1700 insert offers a revamped version of perfect size to provide ambiance and warmth. Give yourself a real haven of peace with an eco-friendly device whose average particle emission rate is prodigiously low at 1.26 g/h!

Inside and out, this insert is engineered from high quality materials that put you at the center of a heating experience for many years: high-density bricks, cast iron door and quiet blower for increased durability. Discover the different options to customize the look of your appliance, available in black or brushed nickel plated: door overlays and faceplate trims.

RECOMMENDED HEATING AREA: 500 - 1,800 sq. ft.*

FIREBOX VOLUME: 1.9 cu. ft.

OVERALL DIMENSIONS: 21 1/4" H x 27 1/8" W x 22 3/8" D

MAXIMUM LOG LENGTH: 18"

Black or brushed nickel faceplate trims



REQUIRED ACCESSORIES

- > Black or brushed nickel cast iron door overlay
- > Faceplate kit Regular (29" X 44") or Large (32" x 50")
- > Black or brushed nickel faceplate trims

OPTIONS

- > Offset liner adaptor
- > 5"Ø fresh air intake kit oval
- > Rigid fire screen
- > 5"Ø fresh air intake register with airtight damper
- > 5"Ø insulated flex pipe for fresh air intake (4', 10' or 25')



*See the complete technical data on pages 29 and 30.