

INEO  
Fireplace  
tool sets  
See page 38



Osburn 2000 with black door overlay and black legs.

Emissions  
1.54 g/h

Optimum efficiency  
77%

Maximum heat output  
75,000 BTU/h

2000

0B02015

BEYOND

CHARM

The Osburn 2000 is one of the most popular unit in the Osburn family of wood stoves. Its cast-iron door, which features the distinctive lines you've come to expect from Osburn, gives it a look combining the contemporary and the traditional. With a 2.4 cubic foot firebox, the Osburn 2000 will delight the most serious of wood stove enthusiasts who want both style and heating power. Also equipped with a 130 CFM blower, the Osburn 2000 is the most sought-after model of the season!

**RECOMMENDED HEATING AREA:** 500 - 2,100 sq. ft.\*

**FIREBOX VOLUME:** 2.4 cu. ft.

**OVERALL DIMENSIONS (PEDESTAL):** 33 1/8" H x 27" W x 29" D

**MAXIMUM LOG LENGTH:** 20"

**REQUIRED ACCESSORIES**

- > Black or brushed nickel door overlay
- > Choice of pedestal, black or brushed nickel cast iron legs with ash pan kit

**OPTIONS**

- > Rigid fire screen
- > Glass ash lip
- > Quick connect thermodisc kit
- > 5"Ø fresh air intake kit
- > 5"Ø fresh air intake register with airtight damper
- > 5"Ø x 4' insulated flex pipe for fresh air intake kit

Choice of legs



Pedestal



\*See the complete technical data on pages 17 and 18. \*\*See note 2 on page 17.