



PAPYRUS
Fireplace tool sets
 See page 38

2000 Insert

OB02016

BEYOND

CHARM

Maximum heat output

75,000 BTU/h

Emissions

1.54 g/h

Optimum efficiency

77 %

Osburn 2000 insert with brushed nickel plated door overlay and trims and regular faceplate kit.

REQUIRED ACCESSORIES

- > Black or brushed nickel steel door overlay
- > Faceplate kit
Regular (29" X 44") or
Large (32" x 50")
- > Black or brushed nickel faceplate trims

OPTIONS

- > Rigid fire screen
- > Heat shield for surround/shelf
- > Cuttable faceplate (32" x 50")
- > 5"Ø fresh air intake kit oval
- > 5"Ø fresh air intake register with airtight damper
- > Offset liner adaptor

With its 2.4 cubic foot firebox, the Osburn 2000 insert offers an alternative to the people who love its freestanding counterpart. The two models share the same high quality combustion properties and many of the same features. The Osburn 2000 comes with a standard high-power, heat-activated 144 CFM blower strategically positioned to redistribute the heat from the firebox into the room. The 2000 model is designed to receive an optional faceplate that can cover a masonry hearth up to 32 inches (81 cm) high and 50 inches (127 cm) wide. The door overlay is available in black or brushed nickel plated finishes. The faceplate trims are available in black or brushed nickel.

RECOMMENDED HEATING AREA: 500 - 2,100 sq. ft.*

FIREBOX VOLUME: 2.4 cu. ft.

OVERALL DIMENSIONS: 23 1/8" H x 28 3/8" W x 26 3/8" D

MAXIMUM LOG LENGTH: 20"

Black or brushed nickel faceplate trims



Montreal
APPROVED
<2.5 g/h

EPA
Approved
2020

*See the complete technical data on pages 29 and 30.