



DUPLEX
Fireplace tool sets
See page 38

Inspire 2000 insert with narrow U shape faceplate.

Emissions
1.54 g/h

Optimum efficiency
77%

Maximum heat output
75,000 BTU/h

INSPIRE 2000 Insert

OB02045

BEYOND

ELEGANCE

This wood insert will bring an unmatched modernism to your decor, in addition to perfectly combining functionality and comfort. The impeccable lines display a timeless style while guaranteeing reliability and durability. The Inspire will charm you as much by its aesthetics as its 77% optimal performance. With its particle emission rate as low as 1.54 g/h and its high-performance combustion system, environmentalists have never been as happy with wood heating. The Inspire Collection celebrates our past and embraces our future as our team is committed more than ever to our industry's contribution to sustainability. A dream opportunity on the latest trends!

RECOMMENDED HEATING AREA: 500 - 2,100 sq. ft.*

FIREBOX VOLUME: 2.4 cu. ft.

OVERALL DIMENSIONS: 25 1/8" H x 30 1/8" W x 21 1/8" D

MAXIMUM LOG LENGTH: 20"

REQUIRED ACCESSORIES

- > Narrow, narrow U shape or cuttable faceplate

OPTIONS

- > Moulded refractory panel kit for insert
- > 5"Ø fresh air intake kit oval
- > 5"Ø fresh air intake register with airtight damper
- > Offset liner adaptor

Narrow faceplate



Narrow U faceplate



Cuttable faceplate



*See the complete technical data on pages 29 and 30.