



INEO
Fireplace tool sets
See page 38

NEW

MATRIX 2700
Tapered insert

OB02700

BEYOND

HEAT

Maximum heat output 80,000 BTU/h	Emissions 1.14 g/h	Optimum efficiency 74%	Matrix 2700 with brushed nickel plated door overlay
-------------------------------------	-----------------------	---------------------------	---

REQUIRED ACCESSORIES

- > Black or brushed nickel cast iron door overlay

OPTIONS

- > Projection kit for insert 2" or 4"
- > Fire screen door
- > Cuttable faceplate (32" x 50")
- > 5"Ø fresh air intake kit oval

Inspired by nature, the Matrix 2700 insert is a fusion of traditional style and technological innovation. Located in the heart of your living space, the generous viewing area of the Matrix 2700 will invite you to sit back, relax and take in the calm and warmth of its flames. Eco-savvy consumers will appreciate its efficient combustion, quality performance and classic beauty.

Customize the look of this non-catalytic appliance by choosing from a black or brushed silver-plated door overlay and fire screen.

RECOMMENDED HEATING AREA: 750 - 2,000 sq. ft.*

FIREBOX VOLUME: 2.5 cu. ft.

OVERALL DIMENSIONS (WITH FACEPLATE): 30 1/8" H x 43 5/8" W x 24 7/8" D

MAXIMUM LOG LENGTH: 20"

Tapered insert for easier installation in masonry hearth



*See the complete technical data on pages 29 and 30.