



STRATFORD II

FIREPLACE

OB04007

With brushed nickel cast iron door overlay and Prairie-style faceplate.

Let yourself be charmed by the timeless beauty of this non-catalytic wood fireplace, which performs particularly well and meets the EPA's most restrictive emissions standards.

The Stratford II offers you more, including a 2.5 cubic foot firebox that's easy to access through double-cast iron doors. This unit will impress you with its distinctive style and exceptional heating capacity. Several options are available, including a air distribution system for heating adjacent rooms (see page 31). With the Osburn Stratford II, there's a world of possibilities waiting for you!

REQUIRED ACCESSORIES

- > Black or brushed nickel cast iron door overlay
- > Traditional or Prairie style faceplate

OPTIONS

- > 4"Ø fresh air intake register with airtight damper
- > Firescreen door
- > Forced air kit
- > Hot air gravity kit

EMISSIONS: 1.14 g/h


RECOMMENDED HEATING AREA: 1,800 - 2,200 sq. ft.

MAXIMUM HEAT OUTPUT: 80,000 BTU/h

FIREBOX VOLUME: 2.5 cu. ft.

COMBUSTION TECHNOLOGY: Non-catalytic

Prairie style faceplate



Traditional style faceplate



See the complete technical data on pages 29 and 30.

EPA