

The 2300 model, one of our new-generation wood stoves, comes from the drawing board to you, backed by the advanced technology of *Solid-Edge*, a 3-D software design program. It features an aesthetically pleasing cast-iron door complete with the Osburn logo, hidden latch and hinges, and extra-large glass window. Each 2300 model is equipped with an ultra-quiet crossflow blower. The secondary air pipes are integrated into the 1/8" stainless steel baffle to give rigidity that withstands even the severest conditions and to ensure combustion of the highest quality. Read on to find out more about the sophisticated qualities and distinctive look of the 2300.

2300

L



2300 with brushed nickel door on legs

Features

Heating capacity	500 to 2300 sq. ft.*
Firebox volume	3,1 cu. ft.
BTU/hr., EPA test wood	30,800
BTU/hr., seasoned cord wood	85,000
Exterior dimensions	31 1/2"H x 23 3/4"W x 30"D
Maximum log length	20"
Ultra-quiet blower with variable speed	Standard
Ash drawer with safety lid	Standard
Mobile home approved	Yes**

(See complete technical data on page 25 and 26)

Options

Door; painted black, golden fire brown, gold or brushed nickel plated
Thermodisc for blower
Pedestal or cast iron legs (painted black, gold or brushed nickel plated)
Adapter for fresh air kit (5" diameter)

* See note 1 on page 26. ** See note 2 on page 26



Ash drawer with safety lid

SSB
Stainless Steel Baffle

