



INEO
Fireplace tool sets
See page 38

INSPIRE 2000

OB02042

BEYOND

ELEGANCE

Maximum heat output
75,000 BTU/h

Emissions
1.54 g/h

Optimum efficiency
77%

Inspire 2000 with
soapstone base kit.

The Inspire offers a style that will surely withstand variable trends with these pure lines of balanced proportions, allowing the brand Osburn to easily compare to European-style products. This more contemporary look is available on steel base, soapstone or even a minimalist base for those who prefer to place the unit directly on a non-combustible surface. Equipped with a 2.4 cubic feet firebox and an outside air intake, this unit will meet the requirements of domestic energy standards, not to mention that a mobile home installation is permitted. The Inspire largely meets EPA requirements with emissions as low as 1.54 g/h.

REQUIRED ACCESSORIES

- > Decorative side panel kit
- > Minimalist, steel or soapstone base kit

OPTIONS

- > Moulded refractory panel kit
- > 130 CFM blower assembly with variable speed control
- > Quick connect thermodisc kit
- > 5"Ø fresh air intake register with airtight damper

RECOMMENDED HEATING AREA: 500 - 2,100 sq. ft.*

FIREBOX VOLUME: 2.4 cu. ft.


OVERALL DIMENSIONS (BASE): 36 9/16" H x 27 7/8" W x 24 15/16" D

MAXIMUM LOG LENGTH: 20"

Steel base kit



Minimalist base kit



*See the complete technical data on pages 17 and 18. **See note 2 on page 17.